

LUFTVÄRDIGHETSDIREKTIV (LVD)

J Instrument Garmin International LVD Nr 2-3208

Sektion 2. Utlandstillverkad flygmateriel

TITEL:

Modifiering av GNS 430.

GÄLLER:

Garmin International GNS 430 partnummer 011-00280-00 med

serienummer enligt bifogad kopia av FAA AD 2001-23-17.

ÅTGÄRD:

Utför åtgärder enligt bifogad kopia av FAA AD 2001-23-17.

TID FÖR ÅTGÄRD:

Inom 6 månader räknat från 28 december, 2001.

UNDERLAG:

Garmin Service Bulletin No. 9905 revision A daterad 17 september, 1999

eller senare utgåva.

REFERENS:

FAA AD 2001-23-17

BESLUTSDATUM:

20 december 2001

LFS

2001:182

Åtgärder enligt LVD utgör nödvändig förutsättning för ifrågavarande flygmateriels luftvärdighet. Referens BCL M 1.11.

Anteckning om åtgärd, som vidtagits i enlighet med LVD, skall införas i teknisk journal för berörd flygmateriel med hänvisning till ifrågavarande LVD-nummer. Angivet underlag refererar till senast gällande revision/utgåva. LVD utges i luftfartsverkets författningssamlingar LFS.

AIRWORTHINESS DIRECTIVE



U.S. Department of Transportation Federal Aviation Administration

Aircraft Certification Service Washington, DC

We post ADs on the internet at "av-info.faa.gov"

The following Airworthiness Directive issued by the Federal Aviation Administration in accordance with the provisions of Title 14 of the Code of Federal Regulations (14 CFR) part 39, applies to an aircraft model of which our records indicate you may be the registered owner. Airworthiness Directives affect aviation safety and are regulations which require immediate attention. You are cautioned that no person may operate an aircraft to which an Airworthiness Directive applies, except in accordance with the requirements of the Airworthiness Directive (reference 14 CFR part 39, subpart 39.3).

2001-23-17 GARMIN International: Amendment 39-12516; Docket No. 99-CE-87-AD.

- (a) What airplanes are affected by this AD? This AD applies to the GNS 430 units that are specified in paragraph (a)(1) of this AD and are installed on aircraft. These GNS 430 units are installed in, but not limited to, aircraft that are certificated in any category and presented in paragraph (a)(2) of this AD:
- (1) GNS 430 Units, part number 011-00280-00: serial numbers 9630001, 96300002, 96300017, 96300028, 96300034, 96300040, 96300068, 96300104, 96300108, 96300122, 96300125, 96300130, 96300142, 96300149, 96300161, 96300165, 96300218, 96300222, 96300232, 96300269, 96300272, 96300308, 96300333, 96300340, 96300348, 96300354, 96300369, 96300372, 96300382, 96300394, 96300411, 96300413, 96300429, 96300437, 96300451, 96300484, 96300485, 96300489, 96300504, 96300506, 96300513, 96300522, 96300549, 96300563, 96300585, 96300587, 96300618, 96300621, 96300624, 96300628, 96300641, 96300653, 96300664, 96300713, 96300734, 96300756, 96300766, 96300781, 96300785, 96300786, 96300808, 96300831, 96300837, 96300842, 96300846, 96300866, 96300870, 96300872, 96300899, 96300916, 96300923, 96300925, 96300929, 96300941, 96300961, 96300984, 96300987, 96301021, 96301108, 96301130, 96301280, and 96301296 through 96303200.
- (2) Aircraft with the GNS 430 Unit Installation (other aircraft could have field approval installations):

TC holder	Airplane models		
Cessna Aircraft Company	172, 182, 206, 208, 210, 401, 402, 404, 406, 411, 414, 414A,		
	421A, 421B, 421C, 425, 441, 500, 550, S550, 552, 560, 560XL,		
	501, 525, and 551.		
Mooney Aircraft	M20, M20A, M20B, M20C, M20D, M20E, M20F, M20G, M20J,		
	M20K, M20L, M20M, M20R, M20S, and M22.		
Raytheon Aircraft Company	Beech Models E33, F33, G33, E33A, F33A, E33C, F33C, 35, 35R,		
-	A35, B35, B35TC, C35, D35, E35, F35, G35, H35, J35, K35,		
	M35, N35, P35, S35, V35, V35TC, V35A, V35A-TC, V35B,		
	V35B-TC, 36, A36, A36TC, 50, B50, C50, D50, D50A, D50B,		
	D50C, D50E, E50, F50, G50, H50, J50, 60, A60, B60, 65-90,		
	65-A90, B90, C90, C90A, C90B, E90, F90, 100, A100, B100,		
	95-55, 95-A55, 95-B55, 95-C55, D-55, E55, 58, 58P, and 58TC.		
Socata	TBM 700.		

The New Piper Aircraft, Inc	J3C-40, J3C-50, J3C-50S (Army L-4, L-4B, L-4H, and L-4J),
	J3C-65 (Navy NE-1 and NE-2), J3C-65S, J3F-50, J3F-50S,
	J3F-60, J3F-60S, J3F-65 (Army L-4D), J3F-65S, J3L, J3L-S,
	J3L-65 (Army L-4C), J3L-65S, J4, J4A, J4A-S, J4E (Army L-4E),
	J5A (Army L-4F), J5A-80, J5B (Army L-4G), J5C, AE-1, HE-1,
	PA-11, PA-11S, PA-12, PA-12S, PA-14, PA-15, PA-16, PA-16S,
	PA-17, PA-18, PA-18A, PA-18A (Restricted), PA-18S,
	PA-18-"105" (Special), PA-18S-"105" (Special), PA-18-"125"
	(Army L-21A), PA-18AS-"125", PA-18S-"125", PA-18-"135"
	(Army L-21B), PA-18A-"135", PA-18A-"135" (Restricted),
	PA-18AS-"135", PA-18S-"135", PA-18-"150", PA-18A-"150",
	PA-18A-"150" (Restricted), PA-18AS-"150", PA-18S-"150",
	PA-19 (Army L-18C), PA-19S, PA-20, P-20S, PA-20-"115",
	PA-20S-"115", PA-20-"135", PA-20S-"135", PA-22, PA-22-108,
	PA-22-135, PA-22S-135, PA-22-150, PA-22S-150, PA-22-160,
	PA-22S-160, PA-24, PA-24-250, PA-24-260, PA-24-400, PA-25,
	PA-25-235, PA-25-260, PA-28-140, PA-28-150, PA-28-151,
	PA-28-160, PA-28-161, PA-28-180, PA-28-235, PA-28S-160,
	PA-28R-180, PA-28S-180, PA-28-181, PA-28R-200,
	PA-28R-201, PA-28R-201T, PA-28RT-201, PA-28RT-201T,
	PA-28-201T, PA28- 236, PA-32R-301 (SP), PA-32R-301 (HP),
	PA-32R-301T, PA-32-301, PA-32-301T, PA-36-285, PA-36-300,
	PA-36-375, PA-38-112, PA-46-310P, and PA-46-350P.

- (b) Who must comply with this AD? Anyone who wishes to operate any aircraft with one of the affected GNS 430 units installed must comply with this AD.
- (c) What problem does this AD address? The actions specified by this AD are intended to prevent external noise from causing inaccurate course deviation displays in the GNS 430 unit's course deviation indicator (CDI) or horizontal situation indicator (HSI). Such displays could result in the pilot making flight decisions that put the aircraft in unsafe flight conditions.
- (d) What actions must I accomplish to address this problem? To address this problem, you must accomplish the following:

Actions	Compliance	Procedures
(1) Modify the affected	Within the next 6 months after	In accordance with the
GNS430 unit to incorporate	December 28, 2001 (the	MODIFICATION
circuitry changes to the	effective date of this AD).	INSTRUCTIONS section of
deviation and flag outputs.	·	GARMIN Service Bulletin No.:
		9905, Revision A, dated
		September17, 1999.
(2) Do not install an affected	As of December 28, 2001 (the	In accordance with the
GNS 430 unit unless it has been	effective date of this AD).	MODIFICATION
modified as required by		INSTRUCTIONS section of
paragraph (d)(1) of this AD.		GARMIN Service Bulletin No.:
		9905, Revision A, dated
		September 17, 1999.

⁽e) Can I comply with this AD in any other way? You may use an alternative method of compliance or adjust the compliance time if:

- (1) Your alternative method of compliance provides an equivalent level of safety; and
- (2) The Manager, Wichita Aircraft Certification Office (ACO), approves your alternative. Submit your request through an FAA Principal Maintenance Inspector, who may add comments and then send it to the Manager, Wichita ACO.

Note: This AD applies to any aircraft with the equipment installed as identified in paragraph (a) of this AD, regardless of whether the aircraft has been modified, altered, or repaired in the area subject to the requirements of this AD. For aircraft that have been modified, altered, or repaired so that the performance of the requirements of this AD is affected, the owner/operator must request approval for an alternative method of compliance in accordance with paragraph (e) of this AD. The request should include an assessment of the effect of the modification, alteration, or repair on the unsafe condition addressed by this AD; and, if you have not eliminated the unsafe condition, specific actions you propose to address it.

- (f) Where can I get information about any already-approved alternative methods of compliance? Contact Roger A. Souter, FAA, Wichita Aircraft Certification Office (ACO), 1801 Airport Road, Room 100, Wichita, Kansas 67209; telephone: (316) 946-4134; facsimile: (316) 946-4407, e-mail: roger.souter@faa.gov.
- (g) What if I need to fly the airplane to another location to comply with this AD? The FAA can issue a special flight permit under sections 21.197 and 21.199 of the Federal Aviation Regulations (14 CFR 21.197 and 21.199) to operate your airplane to a location where you can accomplish the requirements of this AD.
- (h) Are any service bulletins incorporated into this AD by reference? Actions required by this AD must be done in accordance with GARMIN Service Bulletin No.: 9905, Revision A, dated September 17, 1999. The Director of the Federal Register approved this incorporation by reference under 5 U.S.C. 552(a) and 1 CFR part 51. You may obtain copies from GARMIN International, 1200 East 151st Street, Olathe, Kansas 66062. You may view this information at FAA, Central Region, Office of the Regional Counsel, 901 Locust, Room 506, Kansas City, Missouri, or at the Office of the Federal Register, 800 North Capitol Street, NW., suite 700, Washington, DC.
- (i) When does this amendment become effective? This amendment becomes effective on December 28, 2001.

Issued in Kansas City, Missouri, on November 14, 2001.

Michael K. Dahl,

Acting Manager, Small Airplane Directorate, Aircraft Certification Service.

[FR Doc. 01-29325 Filed 11-30-01; 8:45 am]

BILLING CODE 4910-13-U