
Sektion 2. Utlandstillverkad flygmateriel

TITEL: Intervall för underhåll och packning

GÄLLER: Parachute de France modell P512.

ÅTGÄRD: Utför åtgärder angivna i PARACHUTE DE FRANCE Service Bulletin nr 001 daterad 3 maj 1994 eller senare utgåva.

TID FÖR ÅTGÄRD: Inom 10 dagar räknat från detta LVD's utgivningsdatum.

UNDERLAG: PARACHUTE DE FRANCE Service Bulletin Nr 001 daterad 3 maj 1994 eller senare utgåva.

REFERENS: DGAC AD 94-134(AB) (kopia bifogad).

UTGIVNINGS-DATUM: 1994-07-14

LFS: 1994:27

Åtgärd enligt LVD utgör nödvändig förutsättning för ifrågavarande flygmateriels luftvärdighet. Referens BCL M 1.11. Anteckning om åtgärd, som vidtagits i enlighet med LVD, skall införas i teknisk journal för berörd flygmateriel med hänvisning till ifrågavarande LVD-nummer. Angivet underlag refererar till senaste gällande revision/utgåva. LVD utges i luftfartsverkets författningssamlingar LFS.

AIRWORTHINESS DIRECTIVE

released by DIRECTION GENERALE DE L'AVIATION CIVILE

Inspection and/or modifications described below are mandatory. No person may operate a product to which this Airworthiness Directive applies except in accordance with the requirements of this Airworthiness Directive

Translation of 'Consigne de Navigabilité'

ref.: 94-134(AB)

In case of any difficulty, reference should be made to the French original issue.

PARACHUTES DE FRANCE

Emergency parachute

Periodicity of maintenance and packing

The present Airworthiness Directive applies to the emergency parachutes PARACHUTES DE FRANCE models P512.

To state precisely the applicability of the periodicity of maintenance and packing, the following measures are rendered mandatory at the effective date of the present Airworthiness Directive :

Modify as follow the page M4 , paragraph "Periodicity of maintenance procedures and packing" of the "Manuel d'utilisation et de maintenance" P/N 90091133 Issue 4, May 03, 1994 according to PARACHUTES DE FRANCE Service Bulletin N° 001 May 03, 1994.

Periodicity of maintenance procedures and packing :

- One year in standard normal conditions and storage as described hereafter
- If normal storage conditions are not respected, the operator must be adjust the periodicity.

Standard normal conditions and storage :

Textile and others materials used in the construction of the parachutes may be affected or damaged by different elements. During periods when the equipment is not used, the parachutes must be stored in a room where the temperature is kept between 15°C (59° F) and 22°C (71°6 F), while the relative humidity must be kept between 15% and 72%.

,.../...

n/K

June 08, 1994

PARACHUTES DE FRANCE
Emergency parachute

94-134(AB)

Furthermore the parachute must be protected from :

- ultraviolet light and beams,
- excessive heat, 100°C (212° F) and more,
- acid and corrosive agent (keep out of batteries),
- smokes (chlorine or others aggressive materials),
- gnawing animals.

During periods of regular use, it is acceptable to store the parachute in the carrying bag in a room free of humidity and gnawing animals.

Ref. : PARACHUTES DE FRANCE SB 001

EFFECTIVE DATE : JUNE 18, 1994